

Techcote™

Techcote™ is Central Wire's proprietary, non-metallic, soap lubricant coating that enhances consistency and easy removal. Techcote™ is available on wires this a diameter range of 0.022" to .0625".

TechBrite™

A Techbrite™ finish imparts a mirror like finish on bare bright drawn wire. It's This specialty spring wire coating is recommended for applications that require a bright, lustrous appearance. A Techbrite™ finish is available on spring wires with diameters of 0.020" to 0.125".

**Nickel Flash Coatings**

Nickel Coatings offer improved lubricity and greater corrosion resistance for spring wire applications. Available on select alloys and sizes. Call to discuss application and availability.

Copper With Soap

Copper with Soap spring wire coating is available on wires that are drawn with Techcote™ and with diameters from .020" to 0.625".

Alloy	Available Size Range (inches)		
	Techcote™	TechBrite™	Nickel Flash*
302/304	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
316/316L	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
17-7 PH	0.023 – 0.625	0.003 – 0.125	0.023 – 0.625
Inconel 600	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Inconel 625	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Inconel 718	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
X750	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Monel 400	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
K-500	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Hastelloy C276	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
MP35N	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625
Nitronic 50	0.003 – 0.625	0.003 – 0.125	0.003 – 0.625